



XA.5 Series specification and comparison sheet:

Specifications:	XA200.5	XA160.5	XA100.5	XA60.5	XA30.5
Class	A	A	A	A	A
Type	Mono	Mono	Mono	Mono	Stereo
Gain (dB)	26	26	26	26	26
Full Pwr @ 26 dB gain (V)	2.00	1.79	1.41	1.10	0.77
Low Frequency Response	1.5 Hz	1.5 Hz	1.5 Hz	1.5 Hz	1.5 Hz
High Frequency Response	100 KHz	100 KHz	100 KHz	100 KHz	100 KHz
Power Output /ch (8 ohm)	200	160	100	60	30
Power Output /ch (4 ohm)	400	320	200	120	60
Distortion, (1 KHz, full power)	1%	1%	1%	1%	1%
Maximum Output (Volts)	58	52	41	32	23
Maximum Output (Amps)	48	36	28	20	18
Input Impedance (Kohms)	30 / 20	30 / 20	30 / 20	30 / 20	30 / 20
Damping Factor	200	200	200	150	150
Slew Rate (V/uS)	50	50	50	50	50
Output Noise (uV)	200	200	200	200	200
Input CMRR (dB)	-60	-60	-60	-60	-60
DC Offset (V)	0.05	0.05	0.05	0.05	0.05
Leaves Class A at pk Watts:	400	320	200	120	60
Power Consumption (W)	700	600	300	200	200
Temperature (deg C.)	53	53	53	53	53
Dimension (W x H x D) (In.)	19 x 11.2 x 27.5	19 x 11.2 x 22.5	19 x 9.2 x 21.5	19 x 7 x 19.2	19 x 7 x 19.2
Unit Weight (LBS)	159	131	87	62	62
Ship Weight (LBS)	177	148	105	75	75