



X.5 Series specification and comparison sheet:

Specifications:	X1000.5	X600.5	X350.5	X250.5	X260.5	X150.5
Class	AB	AB	AB	AB	AB	AB
Type	Mono	Mono	Stereo	Stereo	Mono	Stereo
Gain (dB)	26	26	26	26	26	26
Full Pwr @ 26 dB gain (V)	4.47	3.46	2.65	2.24	2.2	1.73
Low Frequency Response	1.5 Hz	1.5 Hz	1.5 Hz	1.5 Hz	1.5Hz	1.5 Hz
High Frequency Response	100 KHz	100 KHz	100 KHz	100 KHz	100KHz	100 KHz
Power Output /ch (8 ohm)	1000	600	350	250	260	150
Power Output /ch (4 ohm)	2000	1200	700	500	520	300
Distortion, (1 KHz, full power)	1%	1%	1%	1%	1%	1%
Maximum Output (Volts)	127	99	76	64	64	50
Maximum Output (Amps)	48	36	28	20	20	18
Input Impedance (Kohms)	30 / 20	30 / 20	30 / 20	30 / 20	30 / 20	30 / 20
Damping Factor	200	200	150	150	150	150
Slew Rate (V/uS)	50	50	50	50	50	50
Output Noise (uV)	200	200	200	200	200	200
Input CMRR (dB)	-60	-60	-60	-60	-60	-60
DC Offset (V)	0.05	0.05	0.05	0.05	0.05	0.05
Leaves Class A at pk Watts:	80	80	40	15	5	10
Power Consumption (W)	700	600	600	300	200	200
Temperature (deg C.)	53	53	53	53	53	53
Dimension (W x H x D)	19 x 11.2 x 27.5	19 x 11.2 x 22.5	19 x 11.2 x 22.5	19 x 9.2 x 21.5	19 x 7 x 19.2	19 x 7 x 19.2
Unit Weight (LBS)	183	132	132	88	62	62
Ship Weight (LBS)	203	150	150	105	75	75