



XP Phono specification and comparison sheet:

<b>Specifications</b>	<b>XP-25</b>	<b>XP-15</b>
Gain	53 dB (47 Single-ended)	40 dB @ 1 KHz (MM) max, single ended
-	66 dB (60 SE)	46 dB @ 1 KHz (MM)max, balanced
-	76 dB (70 SE)	71 dB @ 1 KHz (MC) max, single ended
-	-	76 dB @ 1 KHz (MC)max, balanced
RIAA response	plus/minus .1 dB 20-20 KHz	plus/minus .1 dB 20-20 KHz
Distortion	< .005 % THD @ 1mV MC input	< .01 % THD @ 1mV MC input
-	< .002 % THD @ 10mV MM input	< .002 % THD @ 10mV MM input
Maximum Output	22 volts rms.	20 volts rms.
Output Impedance	150/150 ohms	300/300 ohms
Input Impedance	100pF - 750pF on any input	47 K or 1K / 0-650 pF (MM)
-	30 ohm - 47K ohm any input	5 ohm - 47K ohm (MC)
Unweighted Noise	-93 dB ref. 10 mV (MM)	-90 dB ref. 10 mV (MM)
-	-85 dB ref. 1 mV (MC)	-81 dB ref. 1 mV (MC)
Power consumption	25 watts	15 watts
Number of chassis	2	1
Dimensions, each chassis	17"W x 12"D x 4"H	17"W x 12"D x 4"H
Shipping Weight	55 pounds in packing carton	25 pounds in packing carton